



MACHINE PRECISION AXLE CORP.

0.688 Inch | 17.475 Millimeter x 1.469 Inch | 37.3 Millimeter x 1.063 Inch | 27 Millimeter TIMKEN RAK 11/16 Pillow Block Bearings



Bearing No. RAK 11/16

RAK 11/16 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.45
EAN	0087796056602
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	G1011KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row Spherical Normal Duty Low Base With Set Screw
Long Description	2 Bolt Pillow Block; 11/16" Bore; 1-1/16" Base to Center Height; Eccentric Collar



MACHINE PRECISION AXLE CORP.

	Mount; Ball Bearing; Relubricatable; Cast Iron; Double Land Riding Rubber Contact; Non- expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	RAK 11/16
Weight / LBS	1
d	0.688 Inch 17.475 Millimeter
D	1.469 Inch 37.3 Millimeter
Nominal Bolt Center to Center	3.6 Inch 92 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
B	1.063 Inch 27 Millimeter
Actual Bolt Center to Center	3.6 Inch 92Millimeter
Shaft Size d	11/16 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.531 in
Dimension T	0.594 in
Series	Industrial
Weight	1.001 lb
Seal Type	Shroud Seal
Base to Center Height H	26.99 mm
Total Length L	123.8 mm
Total Width A	1.189 in
Bolt Hole Spacing J	92.1 mm



MACHINE PRECISION AXLE CORP.

Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	22.2 mm
Foot Height H1	8.7 mm
Total Height H2	53.2 mm
Dimension L1	41.3 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	13.9 mm
Dimension B1	1.469 in
Static Load Rating	1070 lbf
Dynamic Load Rating	2380 lbf